ROADVISION

- Multi-volt 10-30V DC input & low current draw
- Brighter than conventional incandescent systems
- 100,000 hour LED life span with solid state technology
- Maintenance free >
- Sealed polycarbonate lens & high impact ABS housing
- Waterproof
- Pre-wired with 300mm of sheathed tinned copper cable
- Simple surface or recessed mount design
- ADR/ECE approved for all functions













ADR Approved

ROADVISION's BR135 Series LED rear signal lamps are a versatile solution! Available in a combination lamp or individual Stop/Tail, Indicator & Reverse functions, they deliver the durability of maintenance free LED technology and provide greater for increased safety. Producing more light output than incandescent lamps whilst drawing a fraction of the current, the BR135's are designed to be easily attached with a simple surface mount design. Constructed with durable polycarbonate lenses and high impact ABS housings, these lamps are dust & water proof and totally maintenance free with a lifespan rated at 100,000hrs. With ROADVISION it's FIT & FORGET.

PART NUMBERS



BR135R Stop/Tail Lamp LED 10-30V Surface Mount





Rear Indicator Lamp LED 10-30V Surface Mount



BR135W Reverse Lamp LED 10-30V Surface Mount



BR135AR

Stop/Tail/Ind Lamp LED 10-30V Surface Mount

| SPECIFICATIONS | BR135R | BR135A | BR135W | BR135AR |
|------------------------|---|--------------------------------------|-----------------------------------|--|
| FUNCTIONS | Stop/Tail | Indicator | Reverse | Stop/Tail/Indicator |
| VOLTAGE INPUT | 10-30V DC | 10-30V DC | 10-30V DC | 10-30V DC |
| NUMBER OF LED'S | 18 LED's | 18 LED's | 18 LED's | Indicator - 9 LEDs, Stop/Tail - 9 LEDs |
| CURRENT DRAW AMPS | 0.2/0.05A @ 13.8V | 0.2A @ 13.8V | 0.2A @ 13.8V | Ind - 0.15A, S/T - 0.15/0.05A @ 13.8V |
| DIMENSIONS AXBXC | 135 x 38 x 20mm | 135 x 38 x 20mm | 135 x 38 x 20mm | 135 x 38 x 20mm |
| LENS CONSTRUCTION | Polycarbonate | Polycarbonate | Polycarbonate | Polycarbonate |
| HOUSING CONSTRUCTION | High Impact ABS | High Impact ABS | High Impact ABS | High Impact ABS |
| MOUNTING HOLE /CUT OUT | 80mm Stud Centres | 80mm Stud Centres | 80mm Stud Centres | 80mm Stud Centres |
| CABLE LENGTH | 300mm Tinned Cable | 300mm Tinned Cable | 300mm Tinned Cable | 300mm Tinned Cable |
| ADR APPROVAL | Stop - CRN 49583 Tail - CRN 49584 | CRN 49698 | CRN 49695 | CTA-2021-0001463 |
| WIRING | Earth - White, Stop - Red, Tail - Brown, | Earth - White, Indicator - Yellow | Earth - White, Reverse - Black | Earth - White, Stop - Red, Tail - Brown, Indicator - Yellow |