

RSM5476 SERIES

ROADVISION™

FEATURES

- Multi-volt 10-30V input & low current draw
- Built-in 10 selectable flash patterns
- Last pattern memory recall
- 100,000 hour LED life span with solid state technology
- Maintenance free
- Multi-unit synchronisation
- Simultaneous or alternating flashing
- Weatherproof & vibration resistant
- Super low-profile for discrete applications



LED WORK LAMPS




ROADVISION's RSM5476 Series super low-profile LED strobe modules are simply perfect for discrete applications! Roadvision's super bright LED strobe modules deliver the durability of maintenance free LED technology and greater visibility. Featuring 10 selectable flash patterns, multi-unit synchronisation (simultaneous or alternating flash), aluminium housing and virtually unbreakable polycarbonate lens. Roadvision's RSM5476 Series modules simply take safety lighting to another level, ideal for all your automotive, industrial and agricultural requirements.

PART NUMBERS



SPECIFICATIONS	RSM5476W	RSM5476A
SYNCHRONISATION	Simultaneous & Alternate	Simultaneous & Alternate
FLASH PATTERNS	10	10
INPUT VOLTAGE	10-30 VDC	10-30 VDC
WATTS	18W	18W
NUMBER OF LEDS	6 x 3W	6 x 3W
CURRENT DRAW @ 13.8V	1.5 Amps	1.5 Amps
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	Aluminium	Aluminium
MOUNTING CENTRES	120mm	120mm
DIMENSIONS AXBXC	130 x 28 x 12mm	130 x 28 x 12mm
WIRING	Red - Positive	Red - Positive
	Black - Negative	Black - Negative
	Green - Flash Select & Sync	Green - Flash Select & Sync
	White - Alternate Flash	White - Alternate Flash

LINE DIAGRAM



FLASH PATTERNS

1	Single
2	Single, California Title 13
3	Double
4	Triple
5	Quadruple
6	Quintuple
7	Combination Single/Double
8	Combination Single/Triple
9	Combination Single/Quintuple
10	Strobe
11	Cruise (30% Brightness)

BKT-RSM02
Mounting Bracket

