# **RWL95 SERIES**





THERMAI

MANAGEMENT

7

5 YEAR WARRANTY

## FEATURES

- Multi-volt 10-30V DC input
- Osram LEDs
- Super low current draw
- 50,000 hour LED lifespan with solid state technology
- . Light weight tough die-cast aluminium housing & polycarbonate lens
- Water & dust proof IP67 rated
- Polycarbonate lens
- Light weight thermal conductive plastic housing
- Simple 2 wire installation with integrated Deutsch plug
- Thermal Management Technology
- Over/under voltage, reverse polarity protection
- EMI/EMC radio interference approved

ROADVISION'S RWL95 Series of LED work lights provide high performance in a durable package designed for Australia's toughest environments. With multi voltage input, a super durable lightweight thermal conductive housing and polycarbonate lens, Roadvision's RWL95 Series work lights are suitable for any application. Packing a punch for those on a budget, the RWL95 Series provide worry free operation whilst delivering the biggest bang for your buck with uncompromised performance.

### PART NUMBERS

MULTI-VOLT 10-30 VDC POLYCARB Lens WATERPROOF



#### RWL9505SF

LED Work Light 10-30V Square 5W Flood Beam



#### RWL9510SF

LED Work Light 10-30V Square 10W Flood Beam

| SPECIFICATIONS       | RWL9505SF      | RWL9510SF        |
|----------------------|----------------|------------------|
| BEAM PATTERN         | Flood          | Flood            |
| MAXIMUM LUMENS       | 516lm          | 958lm            |
| INPUT VOLTAGE        | 10-30 VDC      | 10-30 VDC        |
| MAXIMUM WATTS        | 5W             | 10W              |
| NUMBER OF LEDS       | 5 LED's        | 9 LED's          |
| CURRENT DRAW @ 13.8V | 0.45 Amps      | 0.79 Amps        |
| MAXIMUM LUX @ 10M    | 5.5LX          | 17LX             |
| LENS CONSTRUCTION    | Polycarbonate  | Polycarbonate    |
| HOUSING CONSTRUCTION | ABS            | ABS              |
| DIMENSIONS AXBXC     | 71 x 96 x 28mm | 100 x 129 x 34mm |

LINE DIAGRAM - RWL9505SF

30N

OM

30M

30M

OM

30M

10M

17I X

10M

#### LINE DIAGRAM - RWL9510SF

23M

1LX

41M

0.25LX

47M

0.25LX

82M



