



## FEATURES

- RWL1120 Series LED work lamps produces a light output of 526 max lumens
- Flood Beam Pattern
- 2 x 10W LED's produce super white light close to daylight.
- Multi-volt 9-36V DC input & super low current draw
- 50,000 hour LED lifespan with solid state technology
- Light weight tough die-cast aluminium housing & polycarbonate lens
- Simple 2 wire installation
- Over/under voltage, reverse polarity protection & EMI/EMC radio interference approved

LED WORK LAMPS



ROADVISION's RWL1120 Series work lamps work lights suit the most demanding environments. Offering uncompromised performance and energy efficiency, whilst being compact and easy to install, the RWL1120 Series are perfect for applications where space is limited. Complete with a lightweight die-cast housing and polycarbonate lens and two wire installation, the RWL1120 Series provide a high quality, low fuss solution to your lighting requirements.


## PART NUMBERS



**RWL1120F**  
LED Work Light 9-36V Rectangle 20W Flood Beam




**RWL1120FFM**  
LED Work Light 9-36V Rectangle 20W Flood Beam



SPECIFICATIONS	RWL1120F	RWL1120FFM
BEAM PATTERN	120° Flood	120° Flood
MAXIMUM LUMENS	526lm	526lm
INPUT VOLTAGE	9-36 VDC	9-36 VDC
MAXIMUM WATTS	20W	20W
NUMBER OF LEDS	2 x 10W	2 x 10W
CURRENT DRAW @ 13.8V	1.4 Amps	1.4 Amps
MAXIMUM LUX @ 10M	29LX	29LX
LENS CONSTRUCTION	Polycarbonate	Polycarbonate
HOUSING CONSTRUCTION	Die-Cast Aluminium	Die-Cast Aluminium
DIMENSIONS AXBXC	71 x 62 x 55mm	109 x 59 x 55mm

## LINE DIAGRAM - RWL1120F



## LINE DIAGRAM - RWL1120FFM

