

# S7LK PRO SERIES

# ROADVISION



## FEATURES

- S7LK Stealth PRO Series 7" Driving Light
- Dynamic start-up DRL
- Includes Black cover with DRL windows
- Blackout mounting hardware
- 3W Osram LED's produce super white light close to daylight
- Multi-volt 10-30V DC input & low current draw
- 50,000 hour LED lifespan with solid state technology
- Thermal Management Technology
- Light weight tough die-cast aluminium housing & polycarbonate lens
- IP68 & IP69K protection
- Over/under voltage, reverse polarity protection
- EMI/EMC radio interference approved

LOW KELVIN 4000K

LED DRIVING LAMPS




Roadvision's S7LK Stealth PRO Series Driving Lights deliver cutting-edge upgrades and a sleek modern appearance, making them the perfect choice for smaller SUVs and passenger vehicles. Maintaining the contemporary bezel-less design, the S7LK series now features dynamic start-up Daytime Running Lights (DRL) and a stylish black cover with a dedicated DRL window, offering enhanced functionality and aesthetics. When not illuminated, the DRL seamlessly darkens, ensuring a sleek, understated look. Roadvision's S7LK Stealth PRO Series Driving Lights complement the range by featuring a warmer light colour and wider beam pattern, providing better visibility in wet and dusty conditions while dramatically reducing road sign flare. With black mounting hardware, the S7LK series utilizes 16 x 3W Osram LEDs to produce an impressive 4601lm per light and 369mts of beam penetration at 1 lux. Built to withstand the harshest conditions, these lights feature a lightweight yet tough aluminium housing and a durable polycarbonate lens. Powered by Roadvision's Thermal Management Technology, the S7LK series guarantees superior performance and durability in any environment.

## PART NUMBERS



**RDL6701LKD**  
7" LED Driving Light 10-30V Round 74W Combination Beam



SPECIFICATIONS	RDL6701LKD
BEAM PATTERN	Combination
MAXIMUM LUMENS PER LIGHT (PAIR)	4,601lm (9,202lm)
MAXIMUM LUX @ 10M PER LIGHT (PAIR)	1,365lx (2,730lx)
MAXIMUM BEAM DISTANCE @ 1LX PER LIGHT (PAIR)	369m (522m)
INPUT VOLTAGE	10-30VDC
MAXIMUM WATTS	74W
NUMBER OF LEDS	16 x 3W Osram
CURRENT DRAW @ 13.8V	5.3 Amps
LENS CONSTRUCTION	Polycarbonate
HOUSING CONSTRUCTION	Die-Cast Aluminium
WIRING DRIVING LIGHTS	2 Pin Deutsch Plug, Red - Driving Light +Ve, Black - Driving Light -Ve
WIRING DRL HALO	Green Wire +Ve
DIMENSIONS AXBXC	192 x 78 x 195mm

## LINE DIAGRAM

